

**B3 Series**

**B3 1 0 B B 5 49 - C**

Basic series	
B3 series	B3

Engineering level	
C	Current
CL	CSA Current

Operator Function	
<b>3-way</b>	
Single solenoid, 2-position NC - air return	<b>G</b>
Single solenoid, 2-position NO - air return	H
Double solenoid, 2-position	J
Single remote pilot, 2-position NC - air return	<b>K</b>
Single remote pilot, 2-position NO - air return	L
Double remote pilot, 2-position	M
Single solenoid, 2-position NC - air return / spring assist	V
Single solenoid, 2-position NO - air return / spring assist	W
Single remote pilot, 2-position NC - air return / spring assist	X
Single remote pilot, 2-position NO - air return / spring assist	Y
<b>4-way</b>	
Single solenoid, 2-position - air return	1
Double solenoid, 2-position	2
Single remote pilot, 2-position - air return	3
Double remote pilot, 2-position	4
Double solenoid, 3-position - APB	5
Double solenoid, 3-position - CE	6
Double solenoid, 3-position - PC	7
Double remote pilot, 3-position - APB	8
Double remote pilot, 3-position - CE	9
Double remote pilot, 3-position - PC	0
Single solenoid, 2-position - air return / spring assist	E
Single remote pilot, 2-position - air return / spring assist	F

Options	
Blank	None
02	Solenoid rotated 180° - pins down

	Voltage <sup>§</sup>		
	AC		DC
	60Hz	50Hz	
42	24	22	
45			12
<b>49</b>			<b>24</b>
<b>53</b>	<b>120</b>	<b>110</b>	
57	240	230	
XX	Remote pilot - M5 or valve less 15mm solenoid		
YY	Remote pilot - 5/32" (4mm) tube		

Enclosure / lead length	
0	None, remote pilot valve
<b>5</b>	<b>15mm 3-pin DIN 43650C (male only)</b>
X	Valve less 15mm solenoid

Overrides <sup>§</sup>	
<b>0</b>	<b>None, remote pilot valve</b>
<b>B</b>	<b>Flush - non-locking</b>
<b>C</b>	<b>Flush - locking</b>
D	Extended - non-locking
E	Extended - locking
X	Valve less 15mm solenoid

Port size / thread type	
<b>3-way</b>	
<b>1/8" NPT inline</b>	<b>0*</b>
1/8" BSPP "G" inline	5*
<b>4-way</b>	
<b>1/8" NPT inline</b>	<b>0*</b>
1/8" BSPP "G" inline	5*
1/4" NPT subbase	H†
1/8" NPT face mount	T**
<b>Subbase valve less base</b>	<b>V‡</b>

\* Available for use on IEM Manifolds.  
 \*\* 4-way only.  
 † Subbase valves available for 4-way valves only, included base.

Pilot source / pilot exhaust	
<b>0</b>	<b>None, remote pilot valve</b>
<b>B†</b>	<b>Internal - port #1 / vented</b>
E*	Dual pressure - port #3 / vented
K†	External - body / tapped M5
X†	External - manifold / vented

\* Not available for 3-way Valves.  
 † Not available for Remote Pilot Valves.  
 ‡ See Pilot Source Note below.

§ Enclosure '5'  
 - Override / Voltage Availability

S - Standard  
 O - Option

Voltage code	Override code			
	B	C	D	E
42	O	O	-	-
45	O	O	-	-
49	S	S	O	O
53	S	S	O	O
57	O	O	-	-

  

Voltage code	"02" Option			
	B	C	D	E
42	O	O	-	-
45	O	O	-	-
49	S	S	O	O
53	S	S	O	O
57	O	O	-	-

**C**

Inline Valves

Viking Lite

Viking Extreme

"B" Series

Air Saver Unit

ADEX Series

"N" Series

**Pilot Source 'X'**  
 External-Manifold / Vented

**INLINE & SUBBASE Valves -**  
 Only used IF an IEM or 5-Ported Subbase Aluminum Bar Manifold requires a common external pilot signal through the manifold for low pressure / vacuum applications OR when used with Sandwich Regulators.

Most popular.



For inventory, lead time, and kit lookup, visit [www.pdnplu.com](http://www.pdnplu.com)